



vMix MK (Mobile Kit) LPR-325-790V

vMix Live Production, Streaming and Mixing

4K Compatible

The LPR-325-790V is a Mobile Portable Live Production System with rugged aluminum extrusion chassis construction and rubber corner bumper protection. It utilizes the latest Intel Multi- Core processors for the fastest processing with the best value in the market. The unit compacts a 17.3 inch full HD high resolution display with a 1920x1080 monitor. It offers both internal and removable drive spaces. Everything is combined in a portable package with Thunderbolt- USB4, 2.5 Gigabit Ethernet, Audio and a foldable keyboard w/ touchpad.

Rugged Aluminum Construction with rubber corners bumpers	
17.3" display, 1920x 1080 resolution	
Anti-reflection tempered strengthened glass	
Speakers - Built-in amplified 2x 3W speakers	
Multi-language industrial keyboard with touchpad	
Temperature	
Operating	0°C~50°C
Non-Operating	-20°C~60°C
Relative Humidity	
Operating	0°C~50°C
Non-Operating	-20°C~60°C
Approval CE, FCC, RoHS	



vMix is a complete live video production and live streaming software solution. Create, mix, switch, record and live stream professional live productions.

Support for inputs including Cameras, IP Cameras, Video Files, Images, NDI, SRT, Virtual Sets, Titles, Audio, Instant Replay, Video Calls, Zoom Meetings and much more.

The vMix 28 release has added to an already expansive feature list with direct Zoom Integration, Layer Designer, Audio Bus Manager, AV1 Streaming Support, two additional External Outputs and much more.



CONTACT US



CPU	Intel Core i9 (13th Gen) i9-13900KF (24 Core) 3 GHz Processor - 36 MB L3
vMix Version	vMix 4Kl
Operating system	Microsoft Windows 11 Pro 64-bit
Memory	32 GB RAM
Internal storage	1.0TB Pro NVMe
Ethernet, Wireless & Bluetooth	1 x 2.5Gb Ethernet, 2x2 Wi-Fi 6 (802.11 a/b/g/n/ac/ax) - Bluetooth® v5.2
Data interfaces	4 x USB 3.2 Gen2 / 5 x USB 3.2 Gen1 / 8 x USB 2.0 1 x Thunderbolt™ (USB4®) Header
Graphics	NVIDIA GeForce RTX 4070 Ti SUPER Graphic Card - 16 GB PCI Express 4.0 x16 VERTO
Video Files Supported	AVI, MP4, H264, MPEG-2, WMV, MOV and MXF
IP Video inputs /Outputs	1000 x IP -NDI / SRT / 4 X SRT Out
HD-SDI Video Inputs / Outputs	4 X HD-SDI/3G-SDI - In / Out Assignable (8 x HD-SDI <i>Optional</i>)
Video reference	Tri-Sync or Black Burst
Audio	Embedded audio & External audio input
Dimensions (H x W x D)	Mobile Case (D x W x H) 227 x 433 x 372 (mm)
Weight	19.8 lbs (9 kg) approximate
Power supply	850-Watt 80 PLUS Gold Fully Modular ATX PSU (Front to Back Airflow)

Options

00	Upgrade vMix 4K to vMix Pro
01	Professional Replay Controller 
02	(Dual Thunderbolt™ 4 ports (USB-C®), with support for up to five devices in a daisy chain)
03	NDI, SRT & SDI, Bidirectional Encoders
04	PTZ Cameras



CONTACT US



UMC202HD

U-Phoria USB Audio Interface with MIDAS Microphone Preamplifiers

Dimensions (H x W x D) 46.45 x 170 x 125 mm (1.8 x 6.7 x 4.9")



UMC404HD

U-Phoria USB Audio/MIDI Interface with MIDAS Microphone Preamplifiers

Dimensions (H x W x D) 45.81 x 292 x 130 mm (1.78 x 11.5 x 5.1")



CONTACT US

